

Blown Extrusion Film (FFS)

FORM, FILL, SEAL



Film Characters:

Material	Polyethylene
Width	400 - 1000 mm
Thickness	20-220 μ
Printing	4 colors Side Gusseting Embossing

Blown Extrusion Film(FFS)

- ▶ Form
- ▶ Fill
- ▶ Seal



- ▶ Mechanical properties (ASTM-D882) MD/TD
 - ▶ Tensile strength@Yield
 - ▶ Tensile strength@Break
 - ▶ Minimum Elongation@Break
- ▶ Dart drop strength (ASTM-D1709) MD/TD
- ▶ Elmendorf tear strength (ASTM-D1922) MD/TD
- ▶ Hot sealing strength (ASTM-F88)
- ▶ Coefficient of friction C.O.F (ASTM-D1894)
- ▶ Thickness (ISO 8367-2)
- ▶ Bag drop test (ASTM-D959-80)



JAM PARS PLASTIC CO.

EHEMAM JAM

INVESTMENT COMPANIES GROUP

Tehran Office: Unit.4, First Floor, No.1, 10th Alley,
Miremad St., Motahari Ave., Tehran, IRAN
Tel: +98(21) 8854 4306-10
Fax: +98(21) 8874 7150
www.jamparsplastic.com
Email: info@ehtemamjam.com